Mini blender

HR 2860





Philips Domestic Appliances and Personal Care

ServiceManual

PRODUCT INFORMATION :

The applinace has been equipped with a built-in safety lock, that prevents it from functioning, if the accessories have been assembled incorrectly, or have not been assembled at all.

TECHNICAL DATA :

| Motor | : universal, radio / TV interference suppressed |
|-------------------------------------|--|
| Power consumption | : 220 Watt max. |
| Voltage & frequency | : 220 V, 50 Hz |
| Cordset | : 150 cm, double insulated with moulded on plug |
| Speed setting | : 1 speed |
| Blender capacity | : total jar capacity 0.5 L, 0.4 L effective |
| Mills capacity | : total mill capacity 0.2L, 0.1L effective |
| Speeds unloaded | : blender drive shaft 24750 rpm (max) |
| Weight in fancy box | : 1.48 kg |
| Dimensions fancy box (I x w x h) | : 220 mm x 120 mm x 280 mm |
| | |

SERVICE INFORMATION :

The blender coupling (item 5) on the motor shaft has been provided with a customary left-handed thread. The blender coupling can be detached by means of a screwdriver. Block the rotor shaft (after removing the bottom - item 17) by sticking a screwdriver into the slot of the rotor shaft and remove the blender coupling by turnig it right sides.

Automatic resettable cut-out (part of item 9)

This appliance is equipped with an automatic thermal cut-off system. This system will automatically cut off the power supply to the appliance in case of overheating.

If your appliance suddenly stops running:

- Pull the mains plug out of the socket.
- Let the appliance cool down for 30 minutes.
- Put the mains plug into the socket.
- Switch the appliance on again.

This product meets the requirements regarding interference suppression on radio and TV. After the product has been repaired, it should function properly and has to meet the safety requirements as officially laid down at this moment.

Published by Philips Domestic Appliances and Personal Care Printed in the Netherlands

etherlands © Copyright reserved

Subject to modification

4322 277 00981 02/06





Partslist

| Pos. | Description | Service Code |
|------|---------------------|----------------|
| 1 | Blender cap | 9965 000 14352 |
| 2 | Jar lid | 9965 000 14353 |
| 3 | Jar assy | 9965 000 14354 |
| 5 | Blender coupling | 9965 000 14355 |
| 6 | Housing upper part | 9965 000 14356 |
| 7 | Motor rubber | 9965 000 14357 |
| 8 | Insulation film | 9965 000 14358 |
| 9 | Motor | 9965 000 14359 |
| 10 | Safety switch lever | 9965 000 14360 |
| 11 | Switch spring | 9965 000 14361 |
| 12 | Switch assy | 9965 000 14362 |
| 13 | Housing lower part | 9965 000 14363 |
| 14 | On / Off knob | 9965 000 14364 |
| 15 | Capacitor | 9965 000 01057 |
| 16 | Insulation tubing | 9965 000 14365 |
| 17 | Bottom | 9965 000 14366 |

| Pos. | Description | Service Code |
|------|----------------------------|----------------|
| 20 | Wet mill assy | 9965 000 14367 |
| 21 | Dry mill assy | 9965 000 14368 |
| 22 | Container | 9965 000 14369 |
| 23 | Cover | 9965 000 14370 |
| | | |
| 30 | Cordset China | 9965 000 14371 |
| 30 | Cordset Hong Kong | 9965 000 14372 |
| 31 | Wire connector for 2 wires | 9965 000 01056 |
| 32 | Cable tie | 9965 000 14373 |
| А | Screw | |

